



Elitfönster

DoP
Inåtg 3-glas UKH (ETIUL-AL), 40-29-
CE3036101-en

Declaration of Performance:

Product:	Inåtg 3-glas UKH (ETIUL-AL)
Size:	1480/980
Manufacturer:	Inwido Sverige AB, Brogårdsgatan 1, 574 38 Vetlanda
Intended use:	Windows for fitting vertically in domestic and commercial buildings
System of assessment and verification of constancy of performance:	System 3
Harmonized standard:	SS-EN 14351-1:2006+A2:2016
Notified body:	RISE id nr 0402, ift Rosenheim id nr 0757

Performance

Essential properties, Performance

Watertightness:	E1050
Dangerous substances:	NPD
Resistance to wind load:	4C
Load-bearing capacity of safety devices:	Approved
Acoustic performance:	35 dB (-2;-6)
Thermal transmittance:	1,3
Air permability:	4

Radiation properties

Light transmittance (LT):	0,75
Solar factor (g):	0,6

The performance of the product is consistent with the specified performance.
This declaration of performance has been issued in accordance with Regulation (EU) No 305/2011 at the sole responsibility of the manufacturer specified above.

Signed on behalf of the manufacturer:

Name:	Viktor Arvidsson
Date:	2022-02-01
City:	Vetlanda